

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):



BLACK BORDERS

- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

THOMSON
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

My Account | Products

Search: Quick/Number Boolean Advanced

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)Tools: Add to Work File: [Create new Wor](#)View: [INPADOC](#) | Jump to: [Top](#) Go to: [Derwent...](#)[Email](#)Title: **JP4206366A2: FLAT BATTERY**Country: **JP** JapanKind: **A**Inventor: **NAKAI KENJI;**
HIGASHIMOTO KOJI;
HIRONAKA KENSUKE;
HAYAKAWA TAKUMI;
KOMAKI AKIO;
NAKANAGA TAKEFUMI;
TANIGUCHI MASATOSHI;Assignee: **SHIN KOBE ELECTRIC MACH CO LTD.**
OTSUKA CHEM CO LTD.
[News, Profiles, Stocks and More about this company.](#)Published / Filed: **1992-07-28 / 1990-11-30**Application Number: **JP1990000333743**IPC Code: **H01M 10/40; H01M 4/02;**Priority Number: **1990-11-30 JP1990000333743**

Abstract:


... PURPOSE: To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

... CONSTITUTION: On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

... COPYRIGHT: (C)1992,JPO&Japio.

Family: **None**Other Abstract **None**

Info:



[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)

THOMSON
*
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

[Home](#) | [About Delphion](#) | [My Account](#) | [Products](#)
[Search: Quick/Number](#) | [Boolean](#) | [Advanced](#)

The Delphion Integrated View

 Get Now: ☒ PDF | [More choices...](#)

 Tools: [Add to Work File](#) | [Create new Work File](#)

 View: [INPADOC](#) | Jump to: [Top](#) | [Go to: Derwent...](#)
☒ [Email](#)

 Title: **JP4206366A2: FLAT BATTERY**

 Country: **JP** Japan

 Kind: **A**

 Inventor: **NAKAI KENJI;**
HIGASHIMOTO KOJI;
HIRONAKA KENSUKE;
HAYAKAWA TAKUMI;
KOMAKI AKIO;
NAKANAGA TAKEFUMI;
TANIGUCHI MASATOSHI;

 Assignee: **SHIN KOBE ELECTRIC MACH CO LTD.**
OTSUKA CHEM CO LTD.
[News, Profiles, Stocks and More about this company.](#)

 Published / Filed: **1992-07-28 / 1990-11-30**

 Application Number: **JP1990000333743**

 IPC Code: **H01M 10/40; H01M 4/02**

 Priority Number: **1990-11-30 JP1990000333743**

Abstract:

PURPOSE: To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

CONSTITUTION: On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

COPYRIGHT: (C)1992,JPO&Japio.

 Family: **None**

 Other Abstract: **None**

Info:



[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion | [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)



(19)

(11) Publication number: **04**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **02333743**(51) Intl. Cl.: **H01M 10/40 H01M 4/02**(22) Application date: **30.11.90**

(30) Priority:

(43) Date of application
publication: **28.07.92**(84) Designated contracting
states:(71) Applicant: **SHIN KOBE ELECTRIC
LTD.
OTSUKA CHEM CO LT**(72) Inventor: **NAKAI KENJI
HIGASHIMOTO KOJI
HIRONAKA KENSUKE
HAYAKAWA TAKUMI
KOMAKI AKIO
NAKANAGA TAKEFUM
TANIGUCHI MASATOSH**

(74) Representative:

(54) FLAT BATTERY


(57) Abstract:

PURPOSE: To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

CONSTITUTION: On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a

polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

COPYRIGHT: (C)1992,JPO&Japio





(19)

(11) Publication number: **04**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **02333743**(51) Intl. Cl.: **H01M 10/40 H01M 4/02**(22) Application date: **30.11.90**

(30) Priority:	(71) Applicant: SHIN KOBE ELECTRIC LTD OTSUKA CHEM CO LT
(43) Date of application publication: 28.07.92	(72) Inventor: NAKAI KENJI HIGASHIMOTO KOJI HIRONAKA KENSUKE HAYAKAWA TAKUMI KOMAKI AKIO NAKANAGA TAKEFUM TANIGUCHI MASATOSH
(84) Designated contracting states:	(74) Representative:

(54) FLAT BATTERY

(57) Abstract:

PURPOSE: To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

CONSTITUTION: On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a

polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

COPYRIGHT: (C)1992,JPO&Japio

